



Secured by Design Door Technical Information

IDM Doors Ltd Data Sheet 12

GENERAL

- Range of door styles may be produced as illustrated in the SBD Door Design Sheet.
- Fibreglass-faced, SMC (Sheet Moulded Compound) composite door leaf of nominal 44mm thickness.
- Hung in 70mm Pvc-U Eurocell (Logik) 70mm outer frame.
- Low maintenance and high performance.

Door Leaf Fibreglass Facing

- Nominal 2mm thickness both sides of door.
- Compression moulded SMC to various door embossment patterns.
- Smooth or grained surface finish.
- No site finishing required.
- Low maintenance; wipe down with soft cloth and warm water to clean.
- Standard Colour Options; Black; Blue; Green; Red or White (All with White internal face) and also Golden Oak or Rosewood stains – note glazing beads are deglazeable on site.
- Refer to technical data sheet for colourfastness of the door skin and glazing beads.

Door leaf sub-Frame System

- Composite construction engineered sub-frame
- Laminated PVC-U profiles to outer edge laminated to timber inner frame

Core Insulation

- Injected polyurethane foam – CFC free

GLAZING SYSTEM

Cassette Glazing

- ODL Trisys Screw Fix Glazing Cassette glazing system
- Fixings - Trisys Screws ref: 17138000
- Pre-glaze with 24mm thickness double-glazed units, one pane to be 6.8mm Laminate.
- Full range of cassette designs available

HARDWARE

- Winkhaus Trulock and AV2 Multipoint Locks
- Winkhaus Adjustable Keeps
- Non specific level handle as cylinder guard and cylinder to 3 star rating – TS007
- BS rated 1 star 6-Pin Euro Profile Cylinder (Key/Key)
- TS008 Unicorn Letterplate with integral security Cowl



Secured by Design Door Technical Information

- Door Chain
- Urn Knocker (with Viewer) if required
- Numerals (if required)

MANUFACTURING SIZES

Range of standard sizes and trimable options available.

PRODUCT WEIGHTS (Nominal)

Product	Leaf	PVC-U Doorset
Solid	30kg	45kg
½ glazed	35kg	50kg

NOTE: Weights shown provide guidance for handling and may vary due to the wide variety of specification options available

STANDARDS

Building Regulations Part M

- Compatible with Part M compliant Thresholds
- Sizes available to provide 775mm clear openings for wheelchair access

Building Regulations Part L

- When our maximum half glazed cassette is used the glass is still below 50% of the door area and as such does not need to be considered under this regulation. However the door will still comply.

DOORSET U-VALUE

- Maximum doorset U-value: 1.8 W/m²K
(Half glazed layout, which is achieved without Low-E glazing).